## MASONARY MOUNTING REQUIREMENTS FOR VARIOUS AWNING LENGTHS -AWNING ASSEMBLY W/ BRACKET MOUNTS THREADED ROD ASSEMBLY (CEMENTED IN MESH TUBE) – TYP. ALL MASONARY FASTENING -MASONARY WALLMOUNT EXTERIOR MASONARY SIDING -WALL STUD MASONARY WALL −½" S/S WASHER, TYP. -1/2-13 HEX S/S NUT, TYP. bonn MESH TUBE HOUSING -HILTI MASONARY FASTENER TUBE MOUNT-TRANSFER DRILL FROM WALLMOUNT TO MASONARY WALL MASONARY WALL PLATE ASSEMBLY 2 REQUIRED FOR AWNINGS 8-2" THRU 14'-9" THREADED ROD, HEX NUT, AND WASHER ARRANGEMENT FOR MASONARY MOUNT, TYP. ½-13 THREADED ROD CEMENTED INTO MESH TUBE INTERIOR WALLBOARD-MASONARY WALL PLATE ASSEMBLY 3 REQUIRED FOR AWNINGS 16-5" THRU 23' **SECTION A-A** MASONARY WALL PLATE ASSEMBLY 4 REQUIRED FOR AWNINGS 24-6" THRU 32'-9"